

**MPR 6430.1**

**Revision A**

**EFFECTIVE DATE: April 29, 2020**

**EXPIRATION DATE: April 29, 2025**

---

# **MARSHALL PROCEDURAL REQUIREMENTS**

**AS01**

## **LIFTING EQUIPMENT AND OPERATIONS**

**COMPLIANCE IS MANDATORY**

**DIRECTIVE IS UNCONTROLLED WHEN PRINTED**

Verify current version before use at <https://dml.msfc.nasa.gov/directives>

<b>Marshall Procedural Requirements AS01</b>		
<b>Lifting Equipment and Operations</b>	<b>MPR 6430.1</b>	<b>Revision A</b>
	<b>Date: April 29, 2020</b>	<b>Page 2 of 18</b>

### DOCUMENT HISTORY LOG

Status (Baseline/ Revision/ Change/ Revalidation/ Canceled)	Document Revision/ Change	Effective Date	Description
Baseline		12/20/2013	Document converted from MWI 6430.1 to an MPR.
Change	1	4/22/2014	On 4/22/14, at the request of the OPRD, administrative changes were made to update applicable document P4.e to reflect current document and Appendix E to reflect current version of MSFC Form 4561.
Change	2	1/7/2015	On 1/7/15, at the request of the OPRD, administrative changes were made to Appendix E to reflect current version of MSFC Form 4561.
Revision	A	4/29/2020	Added general LDE requirements to chapter 1 and 2 to align with NASA-STD-8719.9B. Added LDE requirements for clarification concerning NCS and OSHA standards and regulations. Updated requirements referencing critical lift requirements, LDEM roles, approvals, and special permissions. Incorporated MAF in applicable wording and requirements. Updated roles and responsibilities to include, LDEM, User organizations, ISB, LSO, and FMO.

<b>Marshall Procedural Requirements AS01</b>		
<b>Lifting Equipment and Operations</b>	<b>MPR 6430.1</b>	<b>Revision A</b>
	<b>Date: April 29, 2020</b>	<b>Page 3 of 18</b>

## TABLE OF CONTENTS

### PREFACE

- P.1 Purpose
- P.2 Applicability
- P.3 Authority
- P.4 Applicable Documents and Forms
- P.5 Measurement/Verification
- P.6 Cancellation

### CHAPTER 1. RESPONSIBILITIES

### CHAPTER 2. LIFTING DEVICES AND EQUIPMENT REQUIREMENTS

- Appendix A Definitions
- Appendix B (Reserved for Acronyms)
- Appendix C (Reserved for Verification Matrix)
- Appendix D Records
- Appendix E Page 2 - MSFC Form 4561

<b>Marshall Procedural Requirements AS01</b>		
<b>Lifting Equipment and Operations</b>	<b>MPR 6430.1</b>	<b>Revision A</b>
	<b>Date: April 29, 2020</b>	<b>Page 4 of 18</b>

## PREFACE

### P.1 PURPOSE

To document Center-specific requirements for using different types of lifting devices and equipment (e.g., overhead cranes, derrick cranes, hoists, hooks, mobile equipment, Hydra-sets; special hoist-supported, personnel lifting devices; slings) in accordance with NPR 8715.3.

### P.2 APPLICABILITY

- a. This MPR applies to Center personnel, programs, projects, and activities, including contractors and resident agencies to the extent specified in their respective contracts or agreements. (“Contractors,” for purposes of this paragraph, include contractors, grantees, Cooperative Agreement recipients, Space Act Agreement partners, or other agreement parties.)
- b. This MPR applies to the Michoud Assembly Facility.
- c. This MPR applies the following: all mandatory actions (i.e., requirements) are denoted by statements containing the term “shall.” The terms “may” or “can” denote discretionary privilege or permission, “should” denotes a good practice and is recommended, but not required, “will” denotes expected outcome, and “are/is” denotes descriptive material.
- d. This MPR applies the following: all document citations are assumed to be the latest version unless otherwise noted.
- e. This MPR applies to the Facilities Management Office (FMO) for overhead and gantry cranes (including top running monorail, underhung, and jib cranes), derricks, and hoists, to the program/project/user organization for special hoist-supported, personnel-lifting devices, Hydra-sets, load measuring devices, hooks, slings and rigging, and jacks (this MPR only applies to jacks used to lift flight hardware or critical lifts), and to the Logistics Services Office (LSO) for mobile aerial platforms, highlift industrial trucks (forklifts); and mobile cranes. It does not address elevators or front-end loaders.

### P.3 AUTHORITY

NPR 8715.3, NASA General Safety Program Requirements

### P.4 APPLICABLE DOCUMENTS AND FORMS

- a. NPR 1400.1, NASA Directives and Charters Procedural Requirements
- b. NRRS 1441.1, NASA Records Retention Schedules
- c. MPR 1440.2, MSFC Records Management Program

<b>Marshall Procedural Requirements AS01</b>		
<b>Lifting Equipment and Operations</b>	<b>MPR 6430.1</b>	<b>Revision A</b>
	<b>Date: April 29, 2020</b>	<b>Page 5 of 18</b>

- d. MWI 3410.1, Personnel Certification Program
- e. MPR 6410.2, Identifying, Packaging, Handling, and Moving Program Critical Hardware
- f. NASA-STD 8719.9, Standard for Lifting Devices and Equipment
- g. MSFC Form 248, Test Preparation Sheet
- h. MSFC Form 4339, Critical Lift Operation Certification
- i. MSFC Form 4561, MSFC Handling Classification Form
- j. MSFC-RQMT-3479, Fracture Control Requirements for Composite and Bonded Vehicle and Payload Structures
- k. MSFC Form 4332 (Crane/Hoist Daily Inspection Checklist)
- l. MSFC Form 4258 (Engine Powered Lift Truck i.e. forklift)
- m. MSFC Form 4328 (Mobile Crane Daily Inspection Checklist)
- n. MSFC Form 4329 (Aerial Lift Pre-start Inspection Checklist)
- o. QD12-LIFT-001 OVERHEAD CRANE and HOIST COMPLIANCE WORK INSTRUCTION
- p. QD12-LIFT-002 MOBILE CRANE COMPLIANCE WORK INSTRUCTION
- q. QD12-LIFT-003 HIGH LIFT INDUSTRIAL TRUCK (FORKLIFT) COMPLIANCE WORK INSTRUCTION

## **P.5 MEASUREMENT/VERIFICATION**

None.

## **P.6 CANCELLATION**

MPR 6430.1 Baseline, Lifting Equipment and Operations, dated December 20, 2013.

*Electronically approved by*

Jody Singer  
Director

<b>Marshall Procedural Requirements</b>		
<b>AS01</b>		
<b>Lifting Equipment and Operations</b>	<b>MPR 6430.1</b>	<b>Revision A</b>
	<b>Date: April 29, 2020</b>	<b>Page 6 of 18</b>

## **CHAPTER 1. RESPONSIBILITIES**

**1.1 The Center Director** designates in writing a Lifting Devices and Equipment Manager (LDEM).

### **1.2 The LDEM:**

1.2.1 Establishes an overall lifting devices program for MSFC and MAF.

1.2.2 Designates in writing a person as the alternate LDEM for MSFC and a person as the alternate LDEM for MAF to assist the LDEM in duties and responsibilities as outlined in NASA STD 8719.9.

1.2.3 Establishes and chairs a MSFC Lifting Devices Committee for MSFC.

1.2.4 Reviews and approves certification packages for lifting devices designating the device as rated for critical lifts.

1.2.5 Reviews and approves critical lift plans.

1.2.6 Reviews and approves all leased LDE before use.

### **1.3 The Safety and Mission Assurance Office (SMA), Industrial Safety Branch (ISB):**

1.3.1 Provides appropriate hazard analyses for cranes to be certified for critical lifts.

1.3.2 Provides LDE certification packages.

- a. QD12-LIFT-001, Overhead Crane and Hoist Compliance Work Instruction
- b. QD12-LIFT-002, Mobile Crane Compliance Work Instruction
- c. QD12-LIFT-003, Highlift Industrial Truck (Forklift) Compliance Work Instruction

1.3.3 Reviews multiple-point lifts and determines if they should be deemed a critical lift.

1.3.4 Reviews and approves critical lift plans and procedures.

1.3.5 Performs Operational Hazard Analysis for each Critical Lift Operation.

1.3.6 Approves an engineering/safety analysis documenting specific lifting devices to be used to perform load tests of slings and rigging.

1.3.7 Certifies individuals to use lifting devices per MWI 3410.1.

1.3.8 The Explosive Safety Officer (ESO) determines if lifts for explosives are critical on a case by case basis.

<b>Marshall Procedural Requirements AS01</b>		
<b>Lifting Equipment and Operations</b>	<b>MPR 6430.1</b>	<b>Revision A</b>
	<b>Date: April 29, 2020</b>	<b>Page 7 of 18</b>

#### **1.4 The FMO:**

1.4.1 Manages fixed lifting systems and related equipment; overhead cranes, derrick cranes, gantry cranes and hoists.

1.4.2 Maintains a records case file for each fixed lifting system.

1.4.3 Establishes a maintenance program for fixed lifting equipment that ensures all requirements of NASA-STD 8719.9 are met. This includes proof load tests, as well as periodic tests and inspections.

1.4.4 Identifies, at the program/project office's request, devices as to whether it can be rated for critical lifts.

1.4.5 Provides the design and installation of all fixed lifting systems.

1.4.6 Is responsible for testing and tagging Below the Hook Equipment, including structural slings, rigging hardware and slings.

*Note: ET has the option for testing and tagging ET's Below the Hook Equipment, unless instructed otherwise.*

#### **1.5 The LSO:**

1.5.1 Manages mobile lifting equipment; mobile cranes, high lift industrial trucks (forklifts), jacks, hydraulic lifting equipment, and mobile aerial lift platforms.

1.5.2 Establishes a maintenance program for mobile lifting equipment that ensures all requirements of NASA-STD 8719.9 are met. This includes proof load tests, as well as periodic tests and inspections.

1.5.3 Maintains a records case file for each mobile lifting device.

1.5.4 Identifies, at the program/project office's request, devices as to whether it can be rated for critical lifts.

1.5.5 Procures all special purpose equipment to include mobile cranes, mobile aerial platforms, special hoist support personnel lifting devices, and high lift industrial trucks (forklifts).

#### **1.6 Program/Project Offices:**

1.6.1 Identifies cranes that require critical lift classification and provide necessary resources to comply with this requirement.

<b>Marshall Procedural Requirements</b>		
<b>AS01</b>		
<b>Lifting Equipment and Operations</b>	<b>MPR 6430.1</b>	<b>Revision A</b>
	<b>Date: April 29, 2020</b>	<b>Page 8 of 18</b>

1.6.2 Determines if the lift is critical or non-critical, refer to Page 2 of MSFC Form 4561, MSFC Handling Classification Form.

1.6.3 Provides critical lift documentation per NASA-STD 8719.9.

### **1.7 User/owner organizations:**

1.7.1 Ensures all lifting equipment is certified and tagged prior to use.

1.7.2 Ensures all lifting equipment operators are familiar with the pertinent operations sections of NASA-STD 8719.9.

1.7.3 Performs and documents daily inspections on LDE as required by NASA-STD 8719.9. Retain inspection documentation per Appendix D of MPR 6430.1.

- a. MSFC Form 4332 (Crane/Hoist Daily Inspection Checklist)
- b. MSFC Form 4258 (Engine Powered Lift Truck i.e. forklift)
- c. MSFC Form 4328 (Mobile Crane Daily Inspection Checklist)
- d. MSFC Form 4329 (Aerial Lift Pre-start Inspection Checklist)

1.7.4 Prepares critical lift plans and submit to ISB and the LDEM for approval.

1.7.5 Prepares operating procedures describing crane operation, rigging equipment, emergency steps, communication requirements, and special requirements including checklists and inspection requirements for each LDE item.

1.7.6 Determines if the lift is critical or non-critical, refer to Page 2 of MSFC Form 4561, MSFC Handling Classification Form.

1.7.7 Acquires load tests for hydra-sets and rigging including the initial proof load test and periodic load tests as required by NASA-STD 8719.9. (See 2.5.6.)

1.7.8 Maintains critical lift equipment certification packages for lifting equipment (overhead crane, hoist, forklift, mobile crane) they own or rent.

1.7.9 Performs or works with FMO and/or LSO in conducting Monthly and annual inspection packages for lifting equipment (overhead crane, hoist, forklift, mobile crane) they own or rent. Inspections shall be done in accordance to NASA STD 8719.9.

*Note: if user/owner organization chooses to conduct monthly or annual inspections on LDE they own or rent, a record/documentation must be kept of these inspections per Appendix D of MPR 6430.1.*

<b>Marshall Procedural Requirements AS01</b>		
<b>Lifting Equipment and Operations</b>	<b>MPR 6430.1</b>	<b>Revision A</b>
	<b>Date: April 29, 2020</b>	<b>Page 9 of 18</b>

## **CHAPTER 2. Lifting Devices and Equipment Requirements**

### **Introduction**

The Lifting Devices and Equipment (LDE) Committee is chaired by the Lifting Devices and Equipment Manager (LDEM) to control the use of different types of lifting devices and equipment (e.g., overhead cranes, derrick cranes, hoists, hooks, mobile equipment, Hydra-sets; special hoist-supported, personnel lifting devices; slings) and meet the requirements of NASA-STD 8719.9.

### **2.1 LDE Load Test Cycles and Inspections (to include rental LDE)**

2.1.1 Load test cycles for critical LDE and slings, except for rigging hardware, shall be performed annually by an approved organization as identified in 2.5.6.

*Note: Load test cycles for critical rigging hardware shall be performed within two years.*

2.1.2 Inspection of critical and non-critical LDE shall be performed every year by an approved organization and/or certified individual.

2.1.3 Non-critical Slings and LDE shall be load tested at least once every four years unless designated as a non-load test sling.

2.1.4 An inspection will be performed on all LDE after a load test and before being placed back into service.

2.1.5 Tagged Equipment shall have a legible tag showing a minimum: unique identification number, Safe Working Load (SWL), load test date, load test expiration date.

*Note: Tags from other centers will be reviewed/approved by the LDEM.*

2.1.6 LDE, including slings and rigging hardware, shall have a separate tag, sticker, or other identification means, showing the annual inspection date and unique identification of the approved organization or certified individual who performed the inspection.

### **2.2 Critical LDE Certification (to include Rental LDE)**

2.2.1 Powered critical LDE, i.e., overhead cranes; mobile cranes; high lift industrial trucks, shall have a certification package prepared by SMA Office, ISB, and approved by the LDEM prior to use for a critical lift.

2.2.2 Certifications shall be performed per QD12-Lift-001, QD12-Lift-002, and QD12-Lift-003 as identified in 1.3.2.

<b>Marshall Procedural Requirements AS01</b>		
<b>Lifting Equipment and Operations</b>	<b>MPR 6430.1</b>	<b>Revision A</b>
	<b>Date: April 29, 2020</b>	<b>Page 10 of 18</b>

2.2.3 The certification package shall be documented by SMA Office and ISB using MSFC Form 4330, MSFC Certification for Lifting Devices and Equipment.

2.2.4 The certification package shall be approved by the LDEM, ISB, FMO. LSO approval is required for packages involving mobile cranes, high lift industrial trucks.

2.2.5 The requirement for critical lift certification is driven by programmatic need. Program/Project offices will identify LDE to be certified and provide the resources to meet critical classification.

2.2.6 The original certification package shall be placed in the records case file by FMO, LSO and/or owner/user organization.

## **2.3 Critical Lifts**

2.3.1 Program/Project and user/owner organizations will identify critical lifts as defined in 1.6.1 above. Page 2 of MSFC Form 4561 is shown in Appendix E.

2.3.2 Lifts determined to be critical shall be documented by the user/owner organization in a detailed lift procedure, Test Preparation Sheet (MSFC Form 248), or MSFC Handling Classification Form (MSFC Form 4561).

2.3.3 Detailed procedures shall be developed for each critical lift by the user/owner organization and approved by the LDEM and ISB.

2.3.4 MSFC Form 4339 shall be filled out by the user/owner organization and attached to each critical lift procedure.

2.3.5 Multiple point lifts involving more than one crane or other lifting device (i.e. powered industrial truck) shall be considered a critical lift unless ISB reviews the lift and determines that critical lift classification is not necessary.

2.3.6 Critical lifts shall not be performed in wind speeds greater than 10MPH sustained and 20MPH gust, unless reviewed and approved by the lift director, ISB and LDEM.

## **2.4 LDE Operations (to include Rental LDE)**

2.4.1 Only operators and riggers listed in CERTRAK shall use LDE.

*Note: In the event CERTRAK becomes unavailable, operators and riggers will be allowed to use LDE with written permission by the SMA office until CERTRAK becomes available.*

<b>Marshall Procedural Requirements AS01</b>		
<b>Lifting Equipment and Operations</b>	<b>MPR 6430.1</b>	<b>Revision A</b>
	<b>Date: April 29, 2020</b>	<b>Page 11 of 18</b>

2.4.2 Operators shall verify that all LDE has current annual inspection and load test tags or markings prior to use. Rigging has tags attached and other LDE has a certification sticker located near the operator controls or disconnect switch.

2.4.3 The first operator on a given shift shall perform a daily inspection and fill out the daily inspection checklist located near the operator controls or disconnect switch.

2.4.3.1 Operators shall verify the daily inspection has been performed within eight hours prior to using LDE.

2.4.5 The operator shall establish an area where the lift will be performed and ensure no unauthorized personnel enter this area by erecting barriers or other means to control access.

## **2.5 LDE Maintenance**

2.5.1 A maintenance program shall be developed for each lifting device and equipment incorporating manufacturer's recommended maintenance and load test information by FMO, user organization or LSO.

2.5.2 A records case file shall be maintained for each powered lifting device and will contain all required records. (See Appendix D.)

2.5.3 Dated certification tags or stickers shall be placed near operator controls or the disconnect switch for each piece of lifting equipment by FMO.

2.5.4 Rigging shall be load tested in accordance with section 2.1

2.5.5 Rigging shall have a tag attached per section 2.1

2.5.6 Load tests for LDE are required on frequencies as stated in 2.1 above. FMO provides this service through the Facility Work Request system. Test Laboratory provides this service through the Test Preparation Sheet (MSFC Form 248) or an outside source may be utilized provided dated and signed documentation is provided. FMO and the Test Laboratory are the only authorized organizations to perform load tests at MSFC.

## **2.6 New LDE**

2.6.1 FMO shall design and install all new fixed lifting systems.

2.6.2 LSO shall review and approve any procurement and/or lease of all special purpose equipment to include mobile cranes, mobile aerial platforms, special hoist support personnel lifting devices, and high lift industrial trucks (forklifts).

<b>Marshall Procedural Requirements</b>		
<b>AS01</b>		
<b>Lifting Equipment and Operations</b>	<b>MPR 6430.1</b>	<b>Revision A</b>
	<b>Date: April 29, 2020</b>	<b>Page 12 of 18</b>

2.6.3 All new slings and rigging equipment shall be provided with proof load documentation by the manufacturer and sent to AS24 at MSFC and AS60 at MAF for initial tagging prior to first use.

## **2.7 Emergency Procedures**

2.7.1 If any event happens during LDE operation such as an un-commanded operation or equipment failure the operator shall:

2.7.1.1 Use the emergency stop, if equipped to cease all lifting operations.

2.7.1.2 Call Facilities Work Control Desk at 256-544-3919 to report the problem.

2.7.1.3 Remain with the LDE and ensure the area remains clear of all unauthorized personnel until the LDE crew arrives.

2.7.1.4 Inform the LDE crew of all details of the incident.

2.7.2 FMO, ISB or LSO will investigate the incident and determine further action to be taken.

<b>Marshall Procedural Requirements</b>		
<b>AS01</b>		
<b>Lifting Equipment and Operations</b>	<b>MPR 6430.1</b>	<b>Revision A</b>
	<b>Date: April 29, 2020</b>	<b>Page 13 of 18</b>

## APPENDIX A

### Definitions

**Critical-Lift.** Lifting and lowering operations with special, high-dollar items (i.e., spacecraft, one-of-a-kind articles, or major facility components) whose loss would have serious programmatic impact. Critical lifts also include operations with special personnel and equipment safety concerns beyond normal lifting hazards.

**Hazard Analysis.** A systematic analysis performed on cranes being qualified to handle loads classified as critical or program-critical hardware. The analysis is required for initial certification to handle critical loads and must be updated, as needed, to reflect any changes in operations or crane configuration. The analysis must determine potential sources of danger, identify most probable failure modes, and recommend resolutions for those conditions found in the hardware-facility-environment-human relationship which could cause loss of life, personal injury, or loss of crane, facility, or load. The analysis must include crane description, reference documentation, severity assessment, and assessment of specified passive and structural components between the hook and the holding brakes.

**Lifting Devices.** For purposes of this instruction, this term is used to refer to overhead and gantry cranes (including top running monorail, underhung, and jib cranes); mobile cranes; derricks; hoists; special hoist-supported, personnel-lifting devices; Hydra-sets; load measuring devices; hooks; slings and rigging; mobile aerial platforms; forklifts; and jacks. It should be noted that NASA-STD 8719.9 uses the terms “lifting device” and “lifting equipment” interchangeably.

**Non-critical lift.** LDE that is used in normal everyday operations is classified as Non-Critical LDE.

**Proof Load Test.** A load test performed prior to first use, after major modification of the load path, or at other prescribed times. This test verifies material strength, construction, and workmanship, and uses a load typically greater than the rated load. The percentage above rated load varies with equipment type.

**Periodic Load Test or Rated-Load Test.** A load test performed at predetermined intervals with a load equal to the rated load. The acceptable tolerance of the periodic load test is +5%/-0%.

<b>Marshall Procedural Requirements AS01</b>		
<b>Lifting Equipment and Operations</b>	<b>MPR 6430.1</b>	<b>Revision A</b>
	<b>Date: April 29, 2020</b>	<b>Page 14 of 18</b>

## **APPENDIX B**

### **Reserved for Acronyms**

CERTRAK: Certificate Tracking Database

ESO: Explosive Safety Officer

FMO: Facility Maintenance Office

ISB: Industrial Safety Board

LDE: Lifting Devices and Equipment

LDEM: Lifting Device and Equipment Manager

LSO: Logistic Safety Officer

NCS: National Safety Center

SMA: Safety and Mission Assurance

SWL: Safe Working Load

<b>Marshall Procedural Requirements AS01</b>		
<b>Lifting Equipment and Operations</b>	<b>MPR 6430.1</b>	<b>Revision A</b>
	<b>Date: April 29, 2020</b>	<b>Page 15 of 18</b>

**APPENDIX C**

**Reserved for Verification Matrix**

<b>Marshall Procedural Requirements AS01</b>		
<b>Lifting Equipment and Operations</b>	<b>MPR 6430.1</b>	<b>Revision A</b>
	<b>Date: April 29, 2020</b>	<b>Page 16 of 18</b>

## **APPENDIX D**

### **Records**

Records are retained in accordance with NRRS 1441.1, and MPR 1440.2. The following records are maintained by the organizations responsible for different types of lifting devices and equipment.

D.1 Design Records are records of engineering review and approval of designs and configuration changes for cranes, hoists, structural slings, and special hoist-supported, personnel-lifting devices. Retain for the life of the equipment, destroy one year after disposal (NRRS 8/56.5/A/1).

D.2 Inspection and Test Records document the completion of required periodic inspections and test activities. Retain records of 2 inspection cycles; destroy records when second subsequent cycle is completed or when no longer needed, whichever is longer (NRRS 8/56.5/A/2).

D.2.1 Nonconformance Reports document deficiencies identified during inspections and tests. These records are maintained for the same period as the associated Inspection and Test Records.

D.2.2 Corrective Action Records are to document the correction of deficiencies identified during inspections and tests. These records are maintained for the same period as the associated Inspection and Test Reports.

D.3 Acceptance Inspection and Test Records document inspections and tests required before placing new or extensively-modified or repaired equipment into service. Retain for the life of the equipment, destroy one year after disposal (NRRS 8/56.5/A/1).

D.4 Critical-Lift Equipment Qualification Records (e.g. MSFC Form 4330, MSFC Certification for Lifting Devices and Equipment) pertain to the qualification of lifting equipment to handle critical loads. Retain for the life of the equipment, destroy one year after disposal (NRRS 8/56.5/A/1).

D.5 Servicing Records document maintenance and adjustment activities performed for lifting equipment. Retain for at least five years; destroy when 5 years old or when no longer needed, whichever is longer (NRRS 8/56.5/A/3).

D.6 Daily inspection checklists. Retain 3 months; destroy when 3 months old or when no longer needed, whichever is later (NRRS 8/56.5/A/4).

D.7 Record Case Files for powered lifting devices are maintained for the life of the equipment. (Reference paragraph 2.5.2.).

D.8 Personnel Certification Records pertain to personnel certification of operators of lifting equipment, as well as material-handling riggers and flagmen for both critical and non-critical lift

<b>Marshall Procedural Requirements</b> <b>AS01</b>		
<b>Lifting Equipment and Operations</b>	<b>MPR 6430.1</b>	<b>Revision A</b>
	<b>Date: April 29, 2020</b>	<b>Page 17 of 18</b>

operations and are maintained by the SMA, ISB, in the SMA CERTRAK database in accordance with MWI 3410.1.

<b>Marshall Procedural Requirements AS01</b>		
<b>Lifting Equipment and Operations</b>	<b>MPR 6430.1</b>	<b>Revision A</b>
	<b>Date: April 29, 2020</b>	<b>Page 18 of 18</b>

## APPENDIX E

### Page 2 - MSFC Form 4561

#### **MSFC HANDLING CLASSIFICATION FORM (Continued)**

<b>CRITICAL-LIFT DECISION PROCESS</b>		
<p>READ BOTH QUESTIONS PRESENTED BELOW AND ANSWER "YES" OR "NO" TO ALL PARTS OF EACH QUESTION. IF ALL OF THE RESPONSES ARE "NO," THE LIFT OPERATION IS CLASSIFIED AS <b>NON-CRITICAL</b>. IF THE RESPONSE TO AT LEAST ONE QUESTION IS "YES," THE LIFT OPERATION IS CLASSIFIED AS <b>CRITICAL</b>.</p>		
<b>1. Does the load to be lifted meet one of the following criteria used to define a critical load?</b>	<input type="checkbox"/> YES	<input type="checkbox"/> NO
1a. Assemblies with close tolerances or delicate construction which could be damaged by improper handling and such resulting damage could compromise a flight vehicle, payload, or the safety of personnel, regardless of whether the item is considered "Flight Hardware." (Reference MPR 6410.2.)	<input type="checkbox"/> YES	<input type="checkbox"/> NO
1b. Equipment, hardware, software, and items returned from space. A special designation by the assigned program office shall be required for a returned item to be handled as Critical. (Reference MPR 6410.2.)	<input type="checkbox"/> YES	<input type="checkbox"/> NO
1c. Lifting or lowering operations with special, high-dollar items (i.e., spacecraft, one-of-a-kind articles, or major facility components) whose loss can have serious programmatic impact. (Reference NASA-STD-8719.9)	<input type="checkbox"/> YES	<input type="checkbox"/> NO
1d. Composite or bonded structures (used in the construction of MSFC manned vehicle or payload hardware) which have been identified as being susceptible to impact damage and are defined as such within the applicable Damage Threat Assessment or Impact Damage Protection Plan. (Reference MSFC-RQMT-3479)	<input type="checkbox"/> YES	<input type="checkbox"/> NO
<b>2. Does the planned lifting or lowering operation involve special personnel and device/equipment safety concerns beyond normal lifting hazards such as the following? (Reference NASA-STD-8719.9)</b>	<input type="checkbox"/> YES	<input type="checkbox"/> NO
2a. Lifting/lowering personnel with cranes.	<input type="checkbox"/> YES	<input type="checkbox"/> NO
2b. Lifting/lowering hazardous materials such as explosives .	<input type="checkbox"/> YES	<input type="checkbox"/> NO
2c. Performing a two-point lift using two or more cranes or lifting devices (i.e., jacks, fork lifts,) to lift/lower a single load (See note below.)	<input type="checkbox"/> YES	<input type="checkbox"/> NO
2d. Operations that require personnel to be beneath a suspended load. (Reference NASA-STD-8719.9, Appendix C.)	<input type="checkbox"/> YES	<input type="checkbox"/> NO
2e. There is a high probability of damage to the lifting device or equipment which can result in significant repair costs and/or schedule delays for future lift operations.	<input type="checkbox"/> YES	<input type="checkbox"/> NO
2f. The mechanics of the lifting and handling operation itself create a high probability of damage to facilities, devices, equipment, and/or the load.		
<p><b>NOTE: AN S&amp;MA ISB REVIEW OF QUESTION 2 WITH A "YES" ANSWER MAY REDUCE THE CRITICALITY OF A SPECIFIC LIFT TO NON-CRITICAL. THIS IS NOT APPLICABLE TO LIFTS DESIGNATED AS "CRITICAL LIFTS" MEETING THE CRITERIA OF QUESTION 1.</b></p>		